

SpareCrux



LL3-TR03-2

Fiber-optic cables

FIBER-OPTIC SENSORS

SICK
Sensor Intelligence.



Ordering information

Type	part no.
LL3-TR03-2	5308055

Included in delivery: BF-WLL160-10 (1), FC (1)

Other models and accessories → www.sick.com/Fiber-optic_cables

Detailed technical data

Features

Device type	Fiber-optic cables	
Functional principle	Through-beam system, consisting of a sender and a receiver	
Fiber-optic head design	Smooth sleeve	
Application	High flexible (static), Robotics (dynamic flexible)	
Compatible fiber-optic amplifiers	GLL70, WLL80, WLL180, GLL170(T)	
Sensing range max.	Depending on the fiber optic amplifier used	
Minimal object diameter	0.1 mm ¹⁾	
Optical fiber head		
Angle of dispersion	60°	
Integrated lens	No	
Compatibility tip adapters	No	
Optical fiber		
Compatibility with infrared light	No	
Optical fiber cable can be shortened	✓	
Adapter end sleeves required	Yes	
Included with delivery	Adapter sleeves, BF-WLL160-10 (1.0 mm) adapter sleeves, FC fiber cutter (5304141)	

¹⁾ Minimum detectable object was determined at optimum measuring distance and optimum setting.

Mechanics

Optical fiber head	Light emission	Axial
	Smooth sleeve diameter	1.5 mm
Optical fiber	Fiber length	2,000 mm
	Bending radius	4 mm
	Dynamic flexibility (robotics)	Yes
Outside diameter, optical fiber cable connection	1 mm	
	Fiber arrangement	Multi-fiber
	Core structure	4 x Ø 0.25 mm Multi-fiber
Material	Optical fiber head	Stainless steel
	Sheath	Polyethylen (PE)

Weight	Fibers	Polymethylmethacrylat (PMMA)
		17 g

Ambient data

Ambient operating temperature	-40 °C ... +70 °C
-------------------------------	-------------------

Sensing ranges with WLL180T

Operating mode 16 µs	60 mm
Operating mode 70 µs	175 mm
Operating mode 250 µs	330 mm
Operating mode 2 ms	750 mm
Operating mode 8 ms	1,100 mm
Note	Sensing ranges related to fiber-optic sensors with type of light: visible red light

Sensing ranges with GLL170

Operating mode 250 µs	140 mm
------------------------------	--------


Sensing ranges with GLL170T

Operating mode 50 µs	150 mm
Operating mode 250 µs	240 mm

Classifications


ECLASS 5.0	27270905
ECLASS 5.1.4	27270905
ECLASS 6.0	27270905
ECLASS 6.2	27270905
ECLASS 7.0	27270905
ECLASS 8.0	27270905
ECLASS 8.1	27270905
ECLASS 9.0	27270905
ECLASS 10.0	27270905
ECLASS 11.0	27270905
ECLASS 12.0	27270905
ETIM 5.0	EC002651
ETIM 6.0	EC002651
ETIM 7.0	EC002651
ETIM 8.0	EC002651
UNSPSC 16.0901	39121528

Dimensional drawing LL3-TR03-02



Dimensions in mm (inch)

Dimensional drawing



Dimensions in mm (inch)

SpareCrux

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations www.sick.com